



MEGANITE-SDS-2015



1. Identification

Product identifier Meganite®

Other means of identification

SDS number 01

Synonyms Not available.

Recommended use Surfacing material for horizontal and vertical applications.

Recommended restrictions Not available.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer/Supplier Meganite Inc.

General Assistance

E-Mail info@meganite.com

Emergency Telephone Contact your local health or emergency authority immediately.

2. Hazard(s) Identification

Classification of the Product: Not classified.

*Classification of the ingredient:

*Note: The product in its finished, marketed form is believed to be inert and generally innocuous. These classifications/hazards are pertaining to a compromised/disrupted product due to operations and processing such as sanding, sawing, grinding, burning etc.

Physical hazards None Known

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Sensitization, Skin Category 1
Specific target organ toxicity, single Category 3

exposure; Respiratory tract irritation

Label elements WARNING!!!



IRRITANT

Signal word Warning



Hazard statement

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.

Precautionary statement

Prevention

Wash skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area.

Response

IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. In case of fire: Use water or

dry chemicals for extinction.

Store in a well-ventilated place. Keep container tightly closed. **Storage**

Store locked up.

Disposal Dispose of contents/container in accordance with

> local/regional/national/international regulations. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded. Allow hot or heated material to solidify

and cool before disposal.

Hazard(s) not otherwise classified

(HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Alumina Trihydrate	21645-51-2	Avg. 60
Acrylic Resin	N/A	Avg. 40
Colorant	N/A	<5



4. First-aid measures

General notes: Consult a physician. Show this safety data sheet to the doctor in

attendance.

Inhalation For overexposure to heated resins, remove from exposure. If

> breathing is difficult, or has stopped, administer artificial respiration (mouth-to-mouth) or oxygen as indicated. Call a

physician, immediately.

Skin contact Wash affected area with soap and plenty of water. Get medical

attention if irritation develops or persists.

Eye contact Immediately flush eyes with plenty of water for at least 15

minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention.

Product in its marketed form is inert. If large amount are Ingestion

swallowed, call physician immediately.

Most important symptoms/effects,

acute and delayed

Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke

and vapors may cause upper respiratory tract irritation.

Symptoms may include burning sensation, coughing, sneezing, and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness, and tearing. This product is not expected to be toxic if ingested. Prolonged or repeated skin contact may lead to allergic skin reactions. Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. May

affect the kidneys and liver.

Indication of immediate medical attention and special treatment needed

General information

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If exposed or concerned: get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash

contaminated clothing before re-use.



5. Fire-fighting measures

Suitable extinguishing media Use water or Dry chemical powder, Carbon dioxide (CO₂) and

Foam.

Unsuitable extinguishing mediaDo not use solid water stream as it may scatter and spread fire.

Fire and Explosion hazard Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a

potential dust explosion hazard.

Hazardous combustion products may include carbon dioxide, carbon monoxide, methyl methacrylate monomer (MMA)

Aldehydes and acrid smoke and fumes.

Special protective equipment and precautions for firefighters

Fire fighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing when fighting fires. Use cold water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Proper personal protective equipment should be utilized when handling this material. See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

If released or spilled, product may be cleaned up and disposed in the trash. Allow hot or heated material to solidify and cool before disposal.

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., cleaning dust surfaces with compressed air). Non-sparking tools should be used.

7. Handling and storage

Handling (Personnel)

Do not breathe dust vapors of fumes that may be evolved during processing. Wash hands before breaks and at the end of workday. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding or inert atmosphere.

Since finished product has sharp edges, protective gloves should be worn when handling.



Conditions for safe storage, including Store in cool dry area. any incompatibilities

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

PEL-TWA

Components **Type** Value

Meganite Acrylic Solid Surface PEL-TWA This product can generate Particulates Not Otherwise

> Regulated (PNOR). The OSHA PEL-TWA for PNOR is 15 mg/m3 (total dust) and 5 mg/m3 (respirable

fraction).

Alumina Trihydrate **PEL-TWA** PNOC - 15 mg/m3 (total dust), 5 mg/m3 (respirable

> fraction) 100 ppm

*Methyl Methacrylate

(CAS#80-62-6)

Components Value Type *Methyl Methacrylate 100 ppm 8-hour TWA

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

(CAS#80-62-6)

US. ACGIH Threshold Limit Values

Components	Type	Value
Meganite 100% Acrylic Resin Solid Surface	TLV-TWA	The TLV-TWA for Particles Not Otherwise Specified (PNOS) is 10 mg/m3 (inhalable) and 3 mg/m3 (respirable fraction).
Alumina Trihydrate	TLV-TWA	PNOC – 10 mg/m3 (inhalable), 3 mg/m3 (respirable fraction)
*Methyl Methacrylate	TLV-TWA	50 ppm
(CAS#80-62-6)	TLV-ST	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
*Methyl Methacrylate	TWA	100 ppm

(CAS#80-62-6)

Where governmentally imposed occupational exposure limits which are lower than the above figures are in effect, such limits shall take precedence.

^{*} Comment: At higher temperatures, small amounts of methyl methacrylate can be released.



Appropriate engineering controls

Local exhaust ventilation should be used to control the emissions of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust dusts, dust collectors, vessels, and processing equipment). Use only appropriately classified electrical equipment and powdered industrial trucks.

Individual protection measures, such as personal protective equipment





Eye/face protection

Employees should be required to wear chemical safety goggles to prevent eye contact. A face shield should be used when appropriate to prevent contact with hot material.

Skin protection & Hand Protection

Since finished material has sharp edges, wear protective gloves when handling.

Additional protection: Wear leather or cotton gloves when grinding, sawing, routing, drilling or sanding.

Other

Polyvinyl alcohol and Teflon protective garments have been recommended for protection against methyl methacrylate. When necessary, garments for protection against heated materials should be used to prevent skin contact with hot acrylate polymer. Emergency eye wash stations and safety showers should be available in the work area.

Respiratory protection

No personal respiratory protective equipment normally required. Wear a NIOSH approved dust respirator that is properly fitted and is in good condition when exposed to dust levels above the ACGIH permissible exposure limits.

Dust safety masks are recommended when the dust concentration is more than 10 mg/m^3 .

Thermal hazards General hygiene considerations

Wear appropriate thermal protective clothing, when necessary. Handle in accordance with good industrial hygiene and safety practice.



9. Physical and chemical properties

Solid. **Appearance** Solid. Physical state **Form** Solid. Color Varies. Odor Odorless. Odor threshold Not available. рΗ Not available. **Melting point** Not available. Freezing point Not applicable.

Initial boiling point and boiling rangeNot available.Flash pointNot applicable.Evaporation rateNot available.

Flammability (solid, gas)Not considered to be flammable.

Upper/lower flammability or explosive limits

Flammability limit – lower (%)
Flammability limit – upper (%)
Explosive limit - lower (%)
Explosive limit - upper (%)
Not applicable.
Not applicable.
Not applicable.
Not available.
Vapor pressure
Vapor density
Relative density
Not available.
Not available.

Solubility(ies)

Solubility (water) Insoluble and also insoluble in Methanol, Diethyl ether, n-

Octanol, Acetone.

Partition coefficient (n-octanol/water)
Percent Volatile
Air (% by volume)
Auto-ignition temperature
Decomposition temperature
Viscosity
Insoluble.
Not applicable.
Not available.
Not available.
Not available.

10. Stability and reactivity

Reactivity Hazardous reactions will not occur under normal conditions.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to avoid Heat - Higher temperature can release methyl methacrylate.

Incompatible materials Not reactive.

Hazardous decomposition Products Carbon dioxide, carbon monoxide, acrid smoke and fumes,

possibly methyl methacrylate.



11. Toxicological information

Product based information: No toxicological information is available for the finished product. This product is generally believed to be inert based on available data.

*Ingredient based information:

*Note: This information are pertaining to a compromised/disrupted product due to operations and processing such as sanding, sawing, grinding, burning etc.

Information on likely routes of exposure:

Ingestion This product is not expected to be toxic if ingested.

Inhalation Harmful if inhaled. Vapors may be irritating to the respiratory

system and nasal passages.

Skin contact Contact of solid with dry skin causes mild irritation.

Eye contact Causes eye irritation and may injure eye tissue if not removed.

Symptoms related to the physical, chemical and toxicological

characteristics:

Burning sensation, coughing, sneezing, and sore throat. Skin redness and itching. Eye burning, redness, and tearing. Prolonged or repeated skin contact may lead to allergic skin reactions. Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness.

Signs and Symptoms of Acute Overexposure:

Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding, or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke and vapor may cause upper respiratory tract irritation. Symptoms may include burning sensation, coughing, sneezing and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness and tearing. This product is not expected to be toxic if ingested.

Signs and Symptoms of Chronic Overexposure:

Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. Prolonged or repeated skin contact may lead to allergic skin reactions.

Medical Conditions Generally Aggravated By Exposure:

Individuals with chronic respiratory disorders may be adversely affected by any fume or airborne particulate matter exposure. Persons with preexisting skin disorders may be more susceptible to the effects of this material.



Numerical measures of toxicity:

21645-51-2)

Methyl Methacrylate (CAS# Oral LD_{50} Rat 7800 mg/kg 80-62-6) Dermal LD_{50} Rabbit > 5000 mg/kg

Inhalation LC₅₀ Rat 15.375 mg/l - 29 mg/l

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Respiratory or skin sensitization

Causes serious eye irritation.

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityBased on available data, the classification criteria are not met.

Carcinogenicity No data available.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity No data available.

Specific target organ toxicity - May cause respiratory irritation.

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard No data available.

Additional information:

*This product may contain certain inorganic pigments that may include compounds of nickel. Certain molecules of nickel have shown sufficient evidence of carcinogenicity (IARC Vol. 49) while others have shown limited or insufficient evidence of carcinogenicity in humans or animals. Titanium Dioxide: In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing with titanium dioxide. Furthermore, human epidemiology studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer. Under normal conditions of use and exposure, toxicological and epidemiological studies for titanium dioxide have shown no significant adverse health effects. Results of an epidemiology study showed that employees who had not been exposed to titanium dioxide were at no greater risk of developing lung cancer than were employees who had been exposed to titanium dioxide. No associations were observed between titanium dioxide exposure and chronic respiratory disease or lung abnormalities. Based on the results of this study, it was concluded that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in work place.



12. Ecological information

Numerical measures of toxicity

Components Test **Species Test Results** Methyl Methacrylate Crustacea EC₅₀ Water flea 69 mg/l, 48 Hours

(CAS# 80-62-6)

Not available. Not available.

Persistence and degradability **Bioaccumulative potential** Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Dispose of in accordance with local, state and federal

> requirements. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded. Allow hot

or heated material to solidify and cool before disposal.

(Daphnia magna)

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methyl Methacrylate (CAS# 80-62-6) Listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard Yes

> Delayed Hazard No Fire Hazard No Pressure Hazard No Reactivity Hazard No

SARA 302 Extremely hazardous substance

Not listed.



SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Methyl Methacrylate (CAS# 80-62-6) Listed
Nickel Compounds Listed

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not listed.

Safe Drinking Water Act (SDWA)

Not listed.

US State regulations:

*Warning, this product contains chemical(s) known to the state of California to cause cancer and/or birth defects or other reproductive harm. The Proposition 65 chemical(s) found in this product appear in trace amounts and would not be expected to pose significant risk: however, a risk assessment for this (these) chemical(s) has not yet been performed. Each product should be assessed in light of its use.

US. Massachusetts RTK - Substance List

Methyl Methacrylate(CAS# 80-62-6)

US. New Jersey Worker and Community Right-to-Know Act

Methyl Methacrylate(CAS# 80-62-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Methyl Methacrylate(CAS# 80-62-6)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed

substance

Nickel Compounds listed.

Canada regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR).

WHMIS classification

D2 Materials Causing Other Toxic Effects.





International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non- Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemical List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01- Jan-2013

Revision date 23-Jul-2015

Version # -

NFPA AND HMIS Ratings NFPA Codes HMIS Codes

Health - 2 Health - 1

Flammability - 0 Flammability - 0 Reactivity - 0 Reactivity - 0



References ACGIH: Documentation of the Threshold Limit Values and Biological

Exposure indices

ECHA: European Chemicals Agency HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

NIOSH: The National Institute for Occupational Safety and Health

NTP: National Toxicology Program NLM: Hazardous Substances Data Base

OECD: Organization for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

Disclaimer: The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

Declare to reader: If you require additional information regarding any legal or regulatory requirements referred to in this SDS, we suggest that you consult with an appropriate regulatory agency, or with a professional with expertise in this area. This information is taken from sources or based upon data believed to be reliable; however, Meganite Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.